

# **GOAL ZERO - VENTURE JUMP**

### 800 AMP JUMP STARTER

#### THE VENTURE JUMP

Never get stuck with a dead car battery again. Designed to revive your battery in an emergency, the new Venture Jump features an 800 amp jump starter to safely bring your vehicle back to life and get you on your way. The Venture Jump also doubles as a power bank to charge phones and USB devices in a pinch. An essential for any commuter, traveler, or off-road adventurer. Compatible with most vehicles up to 6.0L gasoline or 3.0L diesel.

#### **Experience ultimate self-sufficiency**

No more need for roadside assistance. Smart jumper cables make it safe and easy for you to jump start your vehicle battery on your own.

#### All-in-one emergency essential

Integrated LED light illuminates the scene while the 10,000 mAh power bank lets you charge phones and other USB devices on-the-go.

#### **Built to withstand the elements**

IP67 rating ensures protection against dust, sand and debris, and can withstand submersion up to 1 meter of water for at least 30 minutes.

#### **Compact and convenient**

Includes protective carrying case with pockets for convenient, tangle-free cable storage.





Contact Danimex for more information or visit **www.danimex.com/goal-zero** 

DMX-2022-01



## **TECHNICAL SPECIFICATIONS**

VENTURE JUMP SPECS	
Charge times	<ul> <li>USB-C (18W): 3 Hours</li> <li>USB-A (2.4A): 4 Hours</li> <li>Nomad 5: 12-24 Hours</li> <li>Nomad 10: 6-12 Hours</li> <li>Nomad 20: 4-8 Hours</li> </ul>
Ports	<ul> <li>USBA 1 port (output): 5V, up to 2.1A (10.5W max), regulated</li> <li>USBA 2 port (output): 5V/2.1A, 9V/2A, 12V/1.5A (18W max), regulated</li> <li>USBC port (input): 5-9V, up to 2A (18W max), regulated</li> <li>Jump Starter: 12V, 400A starting (800A peak)</li> </ul>
Battery details	<ul> <li>Cell chemistry: Li-ion Polymer</li> <li>Cell capacity: 37Wh (14.8V, 2500mAh)</li> <li>Single Cell Equivalent Capacity: 10000mAh @ 3.7V</li> <li>Lifecycles: Hundreds of cycles</li> <li>Shelf-life: Charge every 3-6 months</li> <li>Fuses: None</li> <li>Management system: Charging and low-battery protection built-in</li> </ul>
General	<ul> <li>Product SKU: 50000</li> <li>IP Rating: IP67</li> <li>Chainable: No</li> <li>Weight (without jumper cable): 17.52oz (497g)</li> <li>Weight (with jumper cable): 24.28oz (688g)</li> <li>Dimensions: 7.1 x 3.9 x 1.5 in (18.1 x 10 x 3.8 cm)</li> <li>Jumper Cable: 14.5 in 10AWG</li> <li>Operating usage temp: -13 - 140F (-25 - 60C)</li> <li>Certs: CE FCC RoHS</li> <li>Warranty: 12 months</li> </ul>
Light	LED (output): 45 Lumens, white LED



